






**Model: FT-600KC**

- ◆ One station Two color/two material
- ◆ Clamping force:60Ton
- ◆ Injection weight:113 g +113g
- ◆ Vertical clamping and Dual- injection system
- ◆ Suitable for producing the product which consist two colors or two material together with Insert Molding process in one machine.

**SPECIFICATION**

		DESCRIPTION	UNIT	FT-600 (射座 1+射座 2)	
INJECTION UNIT		Screw Diameter	mm	φ36	φ36
		Maximum Injection Pressure	kg/cm <sup>2</sup>	1210	1210
		Theoretical Shot Volume	cm <sup>3</sup>	122	122
		Maximum Shot Weight (PS)	g	113	113
		Barrel Heating Power	kW	3.45	3.45
		Nozzle Center Distance	mm	150	
CLAMPING UNIT		Top Platen Size	mm	610×460	
		Bottom Platen Size	mm	660×500	
		Mold Size	mm	460×310	
		Clamping Force	ton	60	
		Minimum Mold Thickness	mm	200/300	
		Opening Stroke	mm	250	
		Open Daylight	mm	450/550	
Ejector Force	ton	1.7			
Ejector Stroke	mm	47			
OTHERS		Hydraulic System Pressure	kg/cm <sup>2</sup>	140	
		Pump/motor Power	hp(kW)	10(7.5)	7.5(5.5)