







Model: FT-800S

- ◆ Single Slide Table
- ◆ Clamping force:80Ton
- ◆ Injection weight:150~266g
- ◆ Vertical clamping and vertical injection design
- ◆ Single Sliding Platen,effective to increase production flexibility and machine safety factor

SPECIFICATION

DESCRIPTION		UNIT	FT-800S			
INJECTION UNIT		Screw Diameter	mm	φ36	φ42	φ48
		Maximum Injection Pressure	kg/cm ²	2074	1523	1166
		Theoretical Shot Volume	cm ³	162	221	289
		Maximum Shot Weight (PS)	g(oz)	150(5.3)	203(7.1)	266(9.4)
		Injection Rate	cm ³ /sec	88	120	157
CLAMPING UNIT		Top Platen Size	mm	700×550		
		Slide Table Size	mm	500×580		
		Slide Stroke	mm	590		
		Mold Size	mm	510×360		
		Clamping Force	ton	80		
		Minimum Mold Thickness	mm	200/300		
		Opening Stroke	mm	270		
OTHERS		Open Daylight	mm	470/570		
		Ejector Force	ton	2.7		
		Ejector Stroke	mm	55		
		Hydraulic System Pressure	kg/cm ²	140		
		Oil Tank Volume	L	390		
		Electric Power	hp(kW)	15(11)		
		Barrel Heating Power	kW	7		
Total Wattage	kW	18				
Machine Dimensions (approx.)	m	2.4×1.3×3.2				
Machine Weight (approx.)	t	3.0				